

ROVSKI 1538

ROVSKI 1538 is a butyl rubber sealing tape for non-critical sealing and waterproof application. ROVSKI 1538 provides economical installation because of its form and ease of handling.

ROVSKI 1538 has some degree of pressure sensitivity and is sufficiently soft for ease of compression during installation. It has good elongation, good weather and ageing resistance. It is permanently flexible and does not harden. It does not stain.

1. Properties

Appearance	White Compound
Specific Gravity (28°C)	1.00 – 1.40
Needle Penetration @ 28°C	60 – 80
Peel Adhesion (kgf/6mm)	0.50 – 1.00
Tensile strength (kgf/cm ²)	0.20 – 0.70
Shear strength (kgf/1.5cm ²)	0.60 – 1.20
Elongation (%)	>1200

2. Application

ROVSKI 1538 is a ready to used tape sealer, reeled up with release paper. It can be used on its own without any lamination or laminated with polyethylene sheet, aluminium sheet or any other material (to be specified) on its precut fixed dimension. Area of application must dry, clean free from dirt and oil.

3. Precaution

1. Store in cool, dry and clean area.
2. Avoid unnecessary exposure to dust.
3. To avoid deformation of tapes do not put heavy objects onto tapes.
4. Shelf life: 12 months (under above storage condition).

4. Dimension and Packing

All sizes and packing available upon request and subjected to arrangement.

****Note:** The information given above is true and is based on our own study and research work and experience. ROVSKI Industries Sdn. Bhd. does not provide warranty or guarantee for products made at different conditions for which are beyond our control. All separate trial cases should be studied and tested to obtain own parameter before any order and delivery.